

THE LATEST IN INFUSION TECHNOLOGY

INTRODUCING THE "Z-PUMP"

Z-800 INFUSION PUMP



THE Z-800 INFUSION PUMP FEATURES:

A SIMPLE, EASY TO USE DESIGN

DURABLE / RELIABLE CONSTRUCTION

ENHANCED PATIENT SAFETY

LOWER COST OF OWNERSHIP

With its simple programming, compact design, advanced engineering, and low cost of operation, the Z-800 is the infusion pump you've been waiting for.

Simple programming and pump operation require less time for training, more time for patient care

- Simple, intuitive design is easy to program and operate
- Requires the fewest programming steps of any similar pump on the market
- Large, easy-to-read display provides all pump information at a glance

Built-in safety features protect patients

- Pump-based free-flow protection; additional set-based free-flow protection also available
- Tamper resistant: Quick one-touch lockout feature
- Alarms include occlusion and air-in-line

Designed with the bottom line in mind

- The Z-800 offers the best value infusion pump on the market today with lowest total cost of ownership
- Lower maintenance costs due to durable design
- Additional long-term cost savings achieved over life of the pump with Zyno administration sets

Ergonomic design is easy to transport, built to last

- Compact size, light weight, cast aluminum casing and robust design features mean the Z-800 is built to last, even in the most punishing environments
- Pump durability translates into significantly lower maintenance costs
- Compact size and light weight means it is easy to transport for both nurses and patients
- Quiet operation

Flexible operation for all your needs

- Multi-Therapy Modes:
 - Continuous with Piggyback
 - Ten Step Sequencing
 - Time and Volume TPN

Upgradeable architecture platform designed for easy future feature enhancements.

Z-800



ZYNO MEDICAL Z-800

Specifications

Mechanism	Linear Peristaltic
Flow Rate Range	1-999 mL/hr
Volume To Be Infused (VTBI)	1-9,999 mL
Accuracy	+/- 5%
Infusion Modes	Continuous and Piggyback, Ten Step Sequencing, and Time and Volume TPN
Free Flow Protection	Pump, and Optional Set-Based Protection
Housing	Cast Aluminum
Weight	5.7 Pounds (2.6 kg)
Size	8.6 x 5.7 x 5.3 in (H/W/D)
Power	110-240 VAC, 50-60Hz
Leakage Current	<100uA
Battery	9.6V, 1.3Ah NiMH (rechargeable)
Battery Operating Time	4 Hours at 125mL/hr
Air In-Line	Ultrasonic. 14 Level Adjustable
Occlusion Pressure	4-30 PSI Adjustable
Tubing	Zyno Needleless, Non-DEHP Standard Tubing
Alarms	Air-in-Line, Occlusion, Door Open, Battery Empty
Warnings	Infusion Complete - KVO, Pump Unattended, Near End, Low Battery



Distributed by:



(p) 800-972-9705

www.innovativemedsys.com

Manufactured by:



Zyno Medical LLC

95 Totten Pond Road, Suite 202

Waltham, MA 02451

(p) 781-895-1988

(f) 781-895-3288

(email) info@zynomed.com

www.zynomed.com



Z-800